

MoorMaster®



Schleuse



MoorMaster®

Reference sites



Picton, New Zealand

- MoorMaster Type I-400
- Ship based automatic mooring system
- Capacity: 4x200 kN (4x20 Tons)
- In operation since 1998 on the vessel "Aratere", a rail passenger ferry



MoorMaster®

Reference sites



Picton, New Zealand

- MoorMaster 400
- Shore based automatic mooring system
- Capacity: 2x400 kN (2x40 tons)
- In operation since 2005



MoorMaster®

Reference sites



Melbourne, Australia

- 2x4 MoorMaster 400
- In operation since 2003



MoorMaster®

Reference sites



Davonport, Australia

- 2x4 MoorMaster 400
- In operation since 2003



MoorMaster®

Reference sites



Port of Dover, UK

- MoorMaster 800
- Shore based automatic mooring system
- Capacity: 1x800 kN (1x80 tons)
- Installed in 2005





MoorMaster®

Reference sites



St. Lawrence, Canada

- MoorMaster 200LS
- Lock based automatic mooring system
- Capacity: 200 kN (20 tons)
- Installation February 2007



MoorMaster®

Reference sites



Salalah, Oman (APM Terminal)

- MoorMaster 600
- Shore based automatic mooring system
- Capacity: 4x600 kN (4x60 tons)
- Installation August 2006




Moormaster®

Market News – Salah Port Services/APMT

- 4 MM600 units commissioned in September 2006
- Khareef trials conducted July to September 2007 this included:
 - *Wave measurement*
 - *Ship Motion measurement*
 - *KPI analysis*




Fore/Aft Surge CORNELIA MSK, Berth 4, Port of Salah, 24th July 2007
Vessel Moored with Ropes & Mooring units or Ropes Only





St. Lawrence Seaways


General information





St. Lawrence Seaways


General information





St. Lawrence Seaways

General information





St. Lawrence Seaways

General information

- Max. ship sizes using the locks are 229m long by 24.3m beam
- On busy days up to 32 vessels can pass a lock
- It takes 9-11 min. to fill/empty 91M litres of water from the lock
- It takes up 15 min. to moor a ship with conventional ropes





MoorMaster®

St Lawrence Seaway – Conventional mooring



- 4 mooring lines out
- 3 shore crew to handle those lines
- All secure after 15 minutes
- Most ships equipped with onboard fenders



MoorMaster®

St Lawrence Seaway

- March 2007 Prototype **MM200LS** commissioned
- 3 months trial on several hundred ships
- Operation in all weather and down to +15° C





MoorMaster®

St Lawrence Seaway – Trial spring 2007

- 51% of all ships successfully moored with MoorMaster®
- 35% not successfully moored due to *special fender list*
- 15% not successful moored due to too *low freeboard* or *special hull shape*





MoorMaster®

St Lawrence Seaway – Future

- 85% will be automatic moored with MoorMaster®
- 15% will be moored with ropes to the bollard on top of the MoorMaster®





MoorMaster®

St Lawrence Seaway – Objectives to auto mooring choice



Barge of 1,500 tonnes securing to mooring bollard on top of the MoorMaster®


- Reduce manual handling of lines
- Reduce safety risk to personnel
- Time saving





MoorMaster®



MM200LS





MoorMaster®

MM200LS



COPYRIGHT 2006 MOORING SYSTEMS LTD
This drawing and model and the rights and privileges in this drawing and model are the property of Mooring Systems Ltd. This drawing and model or any part of it must not be copied, reproduced or



OS-KOM spol. s r.o.
Zdíkovská 22, 150 00 Praha 5
Tel.: 00420 - 257 210 114
Fax: 00420 - 257 211 935
E-mail: oskom@oskom.cz
www.oskom.cz